



CM30

CM30 is designed for workshop use. CM30 is manually operated and easy to use and it comes with a fume exhaust connection.

3-phase and 1-phase electric configurations available.
Please also see product cards for other CM30/35 configurations.

ABSOLUTE
QUALITY
MADE IN
FINLAND

TECHNICAL DATA

Max. hose size (inch) ¹⁾	2 / 1 ¼
Diameter (blade) external (mm)	300x3
Diameter (blade) internal (mm)	30
Max. hose OD (mm)	70
Exhaust outlet OD (mm)	60
Motor Power (kW) ²⁾	3.0/2.2
Motor Power (HP) ²⁾	4.0/2.9
Velocity, 50Hz (rpm)	2750
Velocity, 60Hz (rpm)	3370

DIMENSIONS (LxWxH)

mm	600x503x739
inch	23.6x19.8x29.1

WEIGHT

kg/lbs	42/92.4
--------	---------

MOTOR BRAKE

CM30B is equipped with mechanical brake for faster stopping of blade rotation.

PNEUMATIC PUSHER

CM30P is equipped with pneumatically operated hose pusher.

1) Hydraulic hose, 1-2 wire / 4 wire
2) 3-phase / 1-phase

MODELS


Standard
CM30B
CM30P

STANDARD FEATURES

Toothed blade (part no 12297)

OPTIONS

Smooth blade (part no 12319)



Toothed blade as a standard feature.



Smooth blade as an option.